

S50

SERIES- Ø50mm

迷你型 警示灯 Miniature Signal Light

Q Light



S50B/S50L

S50B | 灯泡 长亮型 警示灯 Bulb Steady Light




灯泡 长亮型的 迷你型 经济型产品

- 灯泡 长亮型
- 适合用于安装空间较小的各类自动化机器、迷你型机床
- 采用受电压变动影响小的特殊灯丝制作的灯泡做光源
- 材质：灯罩-AS, 底座-ABS
- 保护等级：IP44
- Product of bulb steady type
- Miniature product which is suitable for OA machines whose installation space is small and for tiny machines of exclusive use
- Employing the special filament bulb with a weak influence on voltage variation
- Material : Lens-AS, Body-ABS
- Protection class : IP44

型号 Model	电压 Rated Voltage	电流 Current	灯泡 Bulb	重量 Weight	颜色 Color
S50B	DC12V	0.437A	12V5W G14 9S	1 0.08Kg	<div> <div>■ 红-R</div> <div>■ 黄-A</div> <div>■ 绿-G</div> <div>■ 蓝-B</div> </div>
	DC24V	0.290A	24V5W G14 9S	2 0.08Kg	
	AC110V	0.051A	110V5W T16x28 9S	3 0.08Kg	
	AC220V	0.025A	220V5W T16x28 9S	4 0.08Kg	

外形图 (External view drawing)



- 供应电源：电源线 引出型 UL1015-NO.18(0.75sq)x2C 400mm
- DC 产品：黑色线表示负极(-)。
- Power supply : Power line out from the product
UL1015-NO.18(0.75sq)x2C 400mm
- The black line of DC product is negative(-)

结构精巧的迷你型警示灯！

- 采用特殊散光型灯罩提高可见度
- 适合用于安装空间较小的各类自动化机器、迷你型机床
- 适合用于需要经济性的大量生产简易型自动化设备

S50系列产品为了满足需要迷你型产品的客户而生产。

使用在大量生产的简易型自动化设备时发挥高经济性的低价格产品。

According to customers' needs for smaller products, S50 SERIES was developed. In case this product is attached to simple automatic machine producing products in a big quantity, it shows high efficiency at low price.

S50L | LED 长亮/闪亮 警示灯 LED Steady/Flashing Light



高亮度 LED型，适合用于安装空间较小的小型机器

- 高亮度 LED 长亮/闪亮型
- 内装长亮/闪亮选择开关
- 采用使用寿命为半永久性的发光二极管，适合用于震动及冲击较大的设备
- 材质：灯罩-AS, 底座-ABS, 反射镜-耐热性 ABS
- 保护等级：IP44
- Product of steady/flashing, high-brightness LED type
- Having a built-in switch for steady/Flashing selection
- Semi-permanent in the lifespan of light source and suitable for machines having lots of vibration and impact and for places where bulb change is difficult.
- Material : Lens-AS, Body-ABS, Reflector-Heat resisting ABS
- Protection class : IP44

型号 Model	电压 Rated Voltage	电流 Current	重量 Weight	闪亮次数 Flashes Per Min.	颜色 Color
S50L	DC12V	0.040A	0.09Kg	60~80	<div> <div>■ 红-R</div> <div>■ 黄-A</div> <div>■ 绿-G</div> <div>■ 蓝-B</div> </div>
	DC24V	0.047A	0.09Kg		
	AC110V	0.042A	0.10Kg		
	AC220V	0.021A	0.10Kg		

- 供应电源：电源线 引出型 UL1015-NO.18(0.75sq)x2C 400mm
- DC 产品：黑色线表示负极(-)，但产品内部有整流桥，产品不用分正负极。

- Power supply : Power line out from the product
UL1015-NO.18(0.75sq)x2C 400mm
- The black line of DC product is negative(-). But, can connect each line without polarity because bridge circuit is built in.

S50 SERIES 产品指定 (Order Specification)

S50B	-	220	-	G
型号 (Model)		电压 (Voltage)		颜色 (Color)
• S50B		• 12-DC12V		■ R-红(Red)
• S50L		• 24-DC24V		■ A-黄(Amber)
		• 110-AC110V		■ G-绿(Green)
		• 220-AC220V		■ B-蓝(Blue)